

> RESIN BASED SURFACE TREATMENT PRODUCTS



PYE Products..... easy to use



PYE WATER-LOCK

The Waterproof Coating That Protects and Waterproof Masonry Surface

Product Code : WLWE

DESCRIPTION

PYE WATER-LOCK is an Acrylic Based Masonry Waterproofer which is used to solve water seepage problems. It is specially formulated to waterproof interior, exterior, below grade masonry walls, cinder and concrete blocks, stucco and brick, retaining walls, basement walls and foundations.

PYE WATER-LOCK has been tested under GB/T 23445 Hydrostatic Negative Pressure standard. Applied **PYE WATER-LOCK** is paintable over with good quality acrylic paint.

PYE WATER-LOCK directly on bare masonry. Apply first coat with brush or good quality nylon bristle brush in order for **PYE WATER-LOCK** to penetrate into the pores of the masonry. Allow to dry 3 hours between coats. The second coat may be applied by brush or roller. 2 coats are sufficient depending on porosity of the surface/ substrate.

DIRECTIONS FOR USE

Surface preparation

Surface must be clean and free from dirt, dust, grease, oil and paint. Patch evenly all holes or cracks and floor/ wall joints with **PYE AQUA PLUG** or fast setting hydraulic cement. Affected painted water-mark area must be removed by scrapping off or by using **PYE STRIPPA M**. The waterproofing performance of **PYE WATER-LOCK** is highly effective for unpainted surfaces. Not recommended for use on horizontal surface which are subject to foot traffic.

TECHNICAL & PHYSICAL DATA

Colour	White
Form	Semi liquid paste
Adhesion	Adheres firmly to clean, dry and grease free concrete.
Odour	Slight odour, but odourless when dry.
Binder	Acrylic
Coverage	Approx. 1.5s.q. meter per kg for the first coat and up to 2.5s.q. meter per kg for succeeding coats.
Standards	Tested under GB/T 23445 Hydrostatic Negative Pressure standard.
Safety	Non flammable & non toxic.
Cleaning	Clean tools with water.

Application

Stir thoroughly before and during application. Do not thin. Paint only when air and surface is at room temperature or higher. Apply

PACKING

1.5kg, 4kg & 20kg

Further information and advice are freely available from:

PYE PRODUCTS (M) SDN. BHD. (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.