

> **FILLERS PRODUCTS**



PYE

PYE Products..... easy to use



PYEWOOD FILLER

Water-Based Fast Drying Interior Wood Filler

DESCRIPTION

PYEWOOD FILLER is a fast drying, ready-mixed interior wood filler. It is superior to solvent-based plastic woods, is easy to use and shrinkage is minimal. Drying time is approximately 30 minutes in thin layers. It can be painted, stained, or varnished without priming and has an excellent durability resulting in a high quality finish.

SUITABLE FOR

Filling cracks, nail holes and splits in any timber.

DIRECTIONS FOR USE

Surface preparation

Ensure surfaces are clean, dry and free from dirt, grease and loose material.

Application

Mix well before use to ensure a smooth even consistency. Apply with a filling knife or scraper. Slightly overfill the surfaces to allow for sanding back. A wet filling knife will aid in final smoothing. The filled surface has to be dry before sanding, staining or painting. For holes deeper than 6mm, fill in layers allowing each layer to dry before continuing. Always remember to replace the lid firmly when the product is not in use.

Redecorating

PYEWOOD FILLER dries to a natural pine or teak colour and it can be painted without priming. If staining, varnishing or finishing wood to other than natural pine or teak, mix stain or

Product Code : FIWO

paint colorant into the filler to match the wood colour. Test your colour and remember to allow **PYEWOOD FILLER** to dry before checking the colour.

Note: **PYEWOOD FILLER** is not designed for use in wet areas or for gaps that are subject to structural movement. For such application, use acrylic sealants.

TECHNICAL & PHYSICAL DATA	
Adhesion	Excellent adhesion to all types of interior woodwork.
Colour	Natural or Teak
Drying time	A thin film dries in approximately 30mins.
Binder	Acrylic based
Sandability	PYEWOOD FILLER has been formulated with a blend of very fine filler pigments which allows for easy sanding. It is ideal for end grain filling or for obtaining that extra smooth mirror finish on painted surfaces.
Odour	Pleasant
Coverage	10 sq. ft. per 500gm.
Cleaning	Clean tools etc. with water.

PACKING

0.5kg, 1.5kg, 5kg & 25kg

Further information and advice are freely available from:

PYE PRODUCTS (M) SDN. BHD. (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.