

> **FILLERS PRODUCTS**



PYE Products..... easy to use



PYEPUTTY FILLA

Ready Mixed Acrylic-Based Filler

DESCRIPTION

PYEPUTTY FILLA is ready-mixed quick drying filler for filling small cracks and surface defects, particularly where surface may require painting or redecorating. It is also ideal for leveling uneven surface where the tolerance is between 2mm - 5mm in thickness.

Due to its ready-mixed formulation it is time saving with minimal wastage and thus highly economical and convenient to use.

SUITABLE FOR

Cement plaster, concrete brick, emulsion paint, cement paint, asbestos and cembord joint.

DIRECTIONS FOR USE

Surface preparation

Ensure that the surface of cracks and joints are clean, dry and free from dirt, grease and loose materials.

Application

Plasterboard partition & ceiling

Fill the space panels with putty and level flush. Fix reinforced tape over joint and press into fresh putty. Apply 2 coats of **PYEPUTTY FILLA** and level out to smooth surface ready for decoration.

Fine hairline cracks or crazing

Before use, stir the paste well with scrapper. Use the scrapper to press into the fine lines. Slightly overfill the areas and allow to dry before sanding.

Product Code : FIPU

Hollow block wall

Run spatula over surfaces to remove loose materials and joints **PYEPUTTY FILLA**. Apply 2 coats to a thickness of 2 - 3mm, level out to a smooth surface with spatula.

TECHNICAL & PHYSICAL DATA	
Adhesion	Adheres firmly to all clean, dry and grease free plaster and wood surface.
Colour	White
Drying time	A thin film dries in approx. 15 - 30mins. When use for levelling irregular surface, drying time may increase to 1 hour.
Sandability	Formulated for easy sanding.
Odour	Odourless on drying.
Coverage	Approximately 3.36s.q.m per kg.
Cleaning	Clean tools with water.

PACKING

0.5kg, 1.5kg, 5kg & 25kg

Further information and advice are freely available from:

PYE PRODUCTS (M) SDN. BHD. (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.