

> **FILLERS PRODUCTS**



PYE Products..... easy to use



PYESILK-COAT

Silky Plaster Coat

DESCRIPTION

PYESILK-COAT is a high quality, ready-mixed acrylic copolymer resin based plastered coat. It is suitable for use as a smooth plastered coat prior to painting for interior ceilings and walls. It has extra ordinary fungus resistance, excellent penetrative and adhesive power to suit highly alkaline substrates. The surface will not chalk after application and will enhance the coating as smooth as silk.

SUITABLE FOR

Cement plaster, previously painted walls, asbestos, cemboard, prefabricated or precast panels & hard or soft board.

DIRECTIONS FOR USE

Surface preparation

- Make sure that the surface is clean, dry, free of oil, fungus and other impurities.
- Moisture content and pH of the surface applied should be below 8% and pH 9.5 respectively.
- Remove old peeling paint works before applying.

Application

1. Stir thoroughly before use. Add water and stir well if it is too dry.
2. Apply approximately 0.5 - 1.5mm of **PYESILK-COAT** as a plastered coat.
3. Allow the coat to dry (dry time in normal temperature between 20°C - 30°C).
Touch dry: 15 min.
Hard dry: 2 hours
Full hard dry: 4 hours
Re-application interval: 2 hours if required.
4. Sanding: after 5 hours (use sanding paper # 600 - 1000) only if required.
5. For higher sheen, apply two coats of premium interior or exterior paint.

Product Code : FISC

TECHNICAL & PHYSICAL DATA	
Adhesion	Adheres firmly to all surfaces which are clean, dry and grease free. Will not crack or fall out when dry.
Colour	As per colour card.
Coverage	Approximately 50 - 65sq.ft. per kg.
Drying time	A thin film dries in approximately 15 - 30mins when used for leveling irregular surfaces, drying time may vary depending on thickness.
Thickness	Apply approximately 0.5 - 1.5mm as a plaster coat before painting.
Sandability	PYESILK-COAT has been formulated for easy sanding after 5 hours.
Odour	Odourless when dry.
Coverage	Approx. 1.5sq.m @ 16sq.ft./kg.
Storage	Store in cool, dry place.
Cleaning	Clean all equipment with water.

PACKING

1.5kg, 5kg & 25kg

Further information and advice are freely available from:

PYE PRODUCTS (M) SDN. BHD. (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.