

> **FILLERS PRODUCTS**



**PYE**

*PYE Products..... easy to use*



**PYEWALLFILLA**

*Ready Mixed Acrylic Based Filler*

**DESCRIPTION**

**PYEWALLFILLA** is a ready-mixed filler. It is also suitable for use as a smooth plastered coat prior to painting for interior ceilings and walls. It has extraordinary fungus resistance, great whiteness and excellent penetrative and adhesive power to suit highly alkaline substrates. The surface will not chalk after application.

**SUITABLE FOR**

Cement plaster, previously painted walls, asbestos, cement board, prefabricated or precast panels & hard or soft board.

**DIRECTIONS FOR USE**

**Surface preparation**

- Make sure that the surface is clean, dry, free of oil, fungus and other impurities.
- Moisture content and pH of the surface applied should be below 8% and pH 9.5 respectively.
- Remove old peeling paint works before applying.

**Application**

1. Stir thoroughly before use. Use direct or if thinning is required, use clean water.
2. Application can be done by brush or roller by adding 10 to 20% of water and stir well if it is too dry.
3. Allow the coat to dry (dry time in normal temperature between 20°C - 30°C).

**Product Code : FIWA**

- Touch dry: 15min.
- Hard dry: 2 hours
- Full hard dry: 4 hours
- Re-application interval: 2 hours if required.

**TECHNICAL & PHYSICAL DATA**

Adhesion	Adheres firmly to all surfaces which are clean, dry and grease free. Will not crack or fall out when dry.
Colour	White
Coverage	Approximately 4m <sup>2</sup> /kg.
Drying time	A thin film dries in approximately 15 - 30mins when used for leveling irregular surfaces, drying time may vary depending on thickness.
Thickness	Apply approximately 0.5 - 1.5mm as a plaster coat before painting.
Odour	Odourless when dry.
Storage	Store in cool, dry place.
Cleaning	Clean all equipment with water.

**PACKING**

0.5kg & 1.5kg

*Further information and advice are freely available from:*

**PYE PRODUCTS (M) SDN. BHD.** (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



*All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.*