



PYE Products..... easy to use



PYE L-CRACK FILLA

Acrylic Ready-Mixed Filler

DESCRIPTION

PYE L-CRACK FILLA can be used in interior and exterior ready-mixed grey colour quick drying filler with strong adhesion, hardness and minimal shrinkage. It is used for patching 5 - 10mm cracks, holes and surface defects, particularly where surface may require painting or redecorating. It is formulated using special selected filler that is hard and suitable for interior and exterior repairs use and it adheres strongly to cement plaster and concrete surfaces.

SUITABLE FOR

Cement plaster and concrete substrates.

BENEFITS

- Hard
- Excellent adhesion
- Minimal shrinkage
- Easy to apply

DIRECTIONS FOR USE

Surface preparation

Ensure that the surface of cracks is clean, dry and free from dirt, grease and loose materials.

Application

Cracks or Cracking

Apply **PYE L-CRACK FILLA** using scraper to fill in the wide crack hole and remove

Product Code : FICF

any excess filler. Slightly overfill the area and allow it to dry before sanding. Before painting, make sure to clean with a damp cloth after sanding to remove loose particles.

Deep Cracks or Holes

Apply multiple coats of **PYE L-CRACK FILLA** for crack or hole between 10 - 15mm wide or depth with a maximum 7mm per coats, and allow 2 - 3 hours to dry between each coat before patching the next coat.

TECHNICAL & PHYSICAL DATA

Adhesion	Adheres firmly to most clean, dry and grease free concrete surfaces.
Colour	Greyish white
Sandability	Formulated for easy sanding.
Odour	Odourless on drying.
Specific gravity	1.3g/ml
Cleaning	Clean tools with water.

PACKING

0.4kg, 1kg, 4kg & 20kg

Further information and advice are freely available from:

PYE PRODUCTS (M) SDN. BHD. (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.