



PYE Products..... easy to use



## PYESLATE-SEAL

Clear Acrylic Sealer

### DESCRIPTION

**PYESLATE-SEAL** is a specially formulated colourless protecting coating with added Ultra Violet (UV) additive for treatment of interior and exterior cementitious and concrete surfaces against scratching. Ideally, suited for slate, quarry and paver tile, flagstone stamped concrete and concrete tile.

### SUITABLE FOR

**PYESLATE-SEAL** is suitable for all kind of concrete bricks, slates, paves, stone, terra cotta tiles and cementitious substrates.

### DIRECTIONS FOR USE

#### Surface preparation

Ensure surfaces are clean, dry and free from dirt, grease, efflorescence (a whitish substance) that can prevent absorption of the sealer. Any organic growth such as fungi or algae should be treated first with **PYEFUNGIRID**. Repair chip off or concrete surfaces and allow drying before treated. New concrete surface should cure for at least 28 days.

#### Application

Using brush, roller or low-pressure air spray. Apply evenly on all dry dust free

Product Code : RESL

surfaces. For normal application 2 coats are sufficient. However 3 coats may be required for heavy-duty driveway.

Note: **PYESLATE SEAL** cannot be applied to wet or damp surfaces.

### TECHNICAL & PHYSICAL DATA

Colour	Colourless
Form	Liquid
Odour	Solvent odour
Adhesion	Excellent adhesion to clean, dry and sound surfaces.
Drying time	Allow 4 hours between coats.
Coverage	Approx. 7 - 10 sq.m per litre.
Safety	Non-hazardous.
Cleaning	Clean tools and equipments with white spirit after use.

### PACKING

1 litre, 5 litres & 20 litres

Further information and advice are freely available from:

**PYE PRODUCTS (M) SDN. BHD.** (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



BUATAN MALAYSIA

All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.