

> RESIN BASED SURFACE TREATMENT PRODUCTS



**PYE**

*PYE Products..... easy to use*



**PYEWOOD VARNISH**

*Polyurethane Varnish*

**DESCRIPTION**

**PYEWOOD VARNISH** is a clear air-drying polyurethane/ alkyd resin based formula designed to provide a tough wear-resistant finish on all internal timber surfaces in a single can. It gives a satin covering with resistance to water, wear and tear.

**SUITABLE FOR**

Recommended use for parquet, paneling, doors, furniture, interior particleboard, cork tiles etc.

**DIRECTIONS FOR USE**

**Surface preparation**

Clean wood surface with turpentine to remove grease etc. Fill nail holes or defects with **PYE WOODFILLA**. Sand to a smooth finish. Remove dust.

**Application**

Stir thoroughly before application. **PYEWOOD VARNISH** is a ready-to-use product. If however, thinning is required, add 10 - 15% white spirit. Sand lightly between coats. Allow 4 - 6 hours drying time between each coat. Minimum of 2 coats are required but 3 coats are recommended for best results. Light

**Product Code : REWV**

walking traffic is permissible after 12 hours. Drying time may vary, depending on the humidity of the air.

For brush or roller application: use direct or thin with 10% white spirit. For conventional air spray: thin with 10 - 15% white spirit.

**TECHNICAL & PHYSICAL DATA**

Colour	Clear
Form	Viscous liquid
Odour	Solvent odour
Texture	Gloss
Drying time	Allow 4 - 6 hours between coats.
Cleaning	Clean tools and equipment with turpentine.
Storage	Close lid tightly after use.
Fire Risk	Flammable. Keep away from source of ignition.

**PACKING**

250ml, 1 litre, 5 litres & 20 litres

*Further information and advice are freely available from:*

**PYE PRODUCTS (M) SDN. BHD.** (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



BUATAN MALAYSIA

*All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.*