



**PYE**

PYE Products..... easy to use



## PYEWATERPRUF SEALER

*Colourless Silicone Waterproofer*

### DESCRIPTION

**PYEWATERPRUF SEALER** is specially formulated silicone based on silane/ siloxane for impregnating to cement and other porous surfaces. It provides a good penetration capacity and good alkaline resistance.

### SUITABLE FOR

1. All untreated concrete, brick and natural stonework on driveways, patios, walkways and garage floors.
2. *Waterproof the back of Marble or granite*  
**PYEWATERPRUF SEALER** can be applied to the back and sides of the marble or granite. Let the material to cure for 6 hours before installation. This will ensure that no water passes through areas that have been treated thus eliminating watermarks on surface of the marble or granite installation.
3. *Against fungus growth on concrete surface*  
It can be apply as a primer which penetrate into the surface and thus prevent fungus growth.

### DIRECTIONS FOR USE

#### *Surface preparation*

Ensure surfaces are clean, dry and free from dirt, grease, efflorescence (a whitish substance) that can prevent absorption of the sealer. Check all caulking and sealing is fully cured before applying **PYEWATERPRUF SEALER**. The surface to be applied should be dry or damp and not wet. For new concrete surface, a minimum of 28 days is required for curing.

#### *Application*

**PYEWATERPRUF SEALER** is ready to use and dilution is not required. Use a brush, roller or low-pressure air spray to apply. Application of this material will be on flooding action. Apply several coats in wet on wet basis, until the

Product Code : REWS

substrate is saturated. At least 2 or 3 coats are sufficient for all substrates. Do not leave long break between coats.

Apply the next when the substrates have absorbed the previous one and are no longer shiny. Any material that is not absorbed in a few minutes should be wiped up.

Note: **PYEWATERPRUF SEALER** can be applied to dry and damp surfaces but not wet. Allow the surface to air dry after rain. Do not apply **PYEWATERPRUF SEALER** if rain anticipated within 3 hours.

### SPECIFIER'S DESCRIPTION

All work done are in accordance to the manufacturer's recommendation, specification and instructions. **PYEWATERPRUF SEALER** is available from **PYE PRODUCTS (M) SDN.BHD.**

### TECHNICAL & PHYSICAL DATA

Colour	Clear
Form	Liquid
Odour	Solvent odour
Adhesion	Excellent adhesion to clean, damp and sound surfaces.
Coverage	Approx. 1.5 - 3.0sq.m per litre.
Safety	Non-hazardous.
Cleaning	Clean tools and equipment with white spirit after use.

### PACKING

1 litre, 5 litres & 20 litres

Further information and advice are freely available from:

**PYE PRODUCTS (M) SDN. BHD.** (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



MS ISO 9001 REG. NO. 011031-17



BUATAN MALAYSIA

All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.