



PYE

PYE Products..... easy to use



PYEPAVE-KOTE

Waterbased Paving Coat

DESCRIPTION

PYE PAVE KOTE is a waterbased pave coat that provides excellent adhesion and improved appearance on interior or exterior concrete surfaces such as driveways, concrete pavers, concrete floors, rock pools & concrete pots.

DIRECTIONS FOR USE

Surface preparation

- For new/ Untreated porous concrete surfaces:

Allow new concrete to cure for at least 12 weeks before coating. All new or old concrete surfaces must be etched with **PYE CEMENT ETCHER** and rinsed with water.

- For coated concrete surfaces:

Remove all loose flakes and all contaminants such as dirt, grease and oil with **PYE CEMENT ETCHER** followed by sanding for glossy surfaces to provide "key". Before coating, do a compatibility test on small part of intended surface. Allow it to dry for 24 hours and check for lifting of old coating or poor adhesion. If problems are observed total removal of the old coating is required.

Mixing

Stir thoroughly with a broad, flat stirrer before use. Constant stirring is recommended at 5 - 10 minutes intervals.

Product Code : REPK

Application

Dilute **PYE PAVE KOTE** with 5 - 10% water and use as primer if required. Apply two coats to a correctly prepared surface. Lightly sand between coats. Apply using a brush, roller or spray gun. Allow 2 hours drying time between coats.

TECHNICAL & PHYSICAL DATA

Colour	As per colour card.
Form	Liquid
Adhesion	Excellent adhesion to all clean, dry and sound surfaces.
Coverage	8 - 9m ² per litre depending on porosity of surface.
Drying time	Touch dry - ½ hour. Recoat - 2 hours. Hard dry - 24 hours.
Recoating time	2 hours
Thinning	Water
Cleaning	Wash equipment with water immediately after use.

PACKING

1 litre, 4 litres & 18 litres

Further information and advice are freely available from:

PYE PRODUCTS (M) SDN. BHD. (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



BUATAN MALAYSIA

All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.