



PYE

PYE Products..... easy to use



PYE FLOORSHIELD

Acrylic Floor Coating

DESCRIPTION

PYE FLOORSHIELD is a unique single component 100% acrylic water based coating that is not only suitable for most well prepared sound concrete floor surfaces but as well as for asphalt surfaces too. It is designed to have excellent adhesion to concrete and asphalt floor surfaces and provide a tough, durable and UV resistant finish with a good degree of chemical and stain resistance. It uses the best quality of pigments to ensure long lasting colours. **PYE FLOORSHIELD** is suitable for both interior and exterior use.

SUITABLE FOR

- Concrete/ Asphalt floor surfaces
- Driveway
- Parking lots

DIRECTIONS FOR USE

Surface preparation

Floors should be sound, dry and all traces of oil, grease and other foreign matters to be removed. Concrete floors should be well cured and smooth concrete must be etched. Etching can be done using

PYE CEMENT ETCHER.

Mixing

Stir thoroughly with a broad, flat stirrer before use. If necessary dilute up to 10% of clean water to the mixture as the first or primary coat.

Product Code : REFS

Application

Apply using a brush or roller. Normally 2 coats is sufficient and allow a 2 to 4 hour interval between coatings (depending on the humidity and weather). It is best recommended to apply **PYE FLOORSHIELD** in the direction against previous application of the first coat for optimum results. **PYE FLOORSHIELD** should not be applied in conditions of excessive humidity and very hot surfaces. Do not apply when the surface is wet.

TECHNICAL & PHYSICAL DATA

Colour	As per colour card.
Form	Liquid
Adhesion	Excellent adhesion to all clean, dry and sound surfaces.
Coverage	Approx. 2 - 3m ² /kg/ coat depending on the substrate surface.
Drying time	Touch dry - 1 hour. Recoat - 4 hours. Hard dry - 48 hours.
Recoating time	4 hours
Thinning	Water
Cleaning	Wash equipment with water.

PACKING

1.5kg, 4kg & 18kg

Further information and advice are freely available from:

PYE PRODUCTS (M) SDN. BHD. (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



BUATAN MALAYSIA

All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.