

> PROTECTIVE WATERPROOF COATING PRODUCTS



PYE Products..... easy to use



PYEWATER-SEAL
Acrylic Waterproof Sealer

DESCRIPTION

PYEWATER-SEAL is a one-part flexible waterproof sealer based on modified acrylic polymers. It provides an excellent waterproof film on interior and exterior surfaces, preventing water penetration to the underlying substrate, which is normally subject to rain penetration and rising dampness. It effectively obliterates watermarks.

SUITABLE FOR

PYEWATER-SEAL can be applied to interior and exterior wall surfaces in basements, bathrooms, toilets, to retaining walls, floors, lift-wells etc. It is excellent for use on fresh concrete after it has hardened.

Suggested applications include

- Concrete ceilings/ under balconies where moisture seepage is a problem.
- Newly plastered or concrete surface as an undercoat prior to painting.
- Interior walls of water tanks or concrete fish ponds.

DIRECTIONS FOR USE

Surface preparation

Surfaces should be clean, free from dirt and grease.

Mixing

Add about 5 - 10% thinner. Stir well before application. Do not mix with water or other materials. Close lid after use to prevent drying.

Product code: PRWS

Application

PYEWATER-SEAL is easy to apply and can be decorated with emulsion and gloss paints within 2 hours. Apply 2 coats allowing a minimum of 1 hour drying time between coats. Do not sand down topcoat until coating has cured for at least 2 hours.

PYEWATER-SEAL can be applied like conventional paint with brush, roller or spray gun. Always apply generously to ensure good coverage and proper film formation.

TECHNICAL & PHYSICAL DATA	
Colour	White, other tints available.
Form	Semi-viscous liquid.
Odour	Solvent smells but harmless.
Drying time	1 - 2 hours
Coverage	Approx. 5sq.m or 54sq.ft per coat depending on the porosity of the surfaces.
Safety	Non-hazardous.
Cleaning	Clean tools and equipment with thinner.

PACKING

1 litre, 5 litres & 20 litres

Further information and advice are freely available from:

PYE PRODUCTS (M) SDN. BHD. (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.