



PYE

PYE Products..... *easy to use*



PYEACRYL CM

Bonding Agent for Cement Mixes

DESCRIPTION

PYEACRYL CM is a specially formulated white liquid cement modifier made from high performance acrylic polymers. It is designed for use as a high strength admixture and bonding agent for Portland cement. It provides improved resistance to impact, abrasion, moisture and attack by acids and other water-soluble chemicals. Improved cement hydration and its bonding properties result in a high strength mortar that is effective in its application down to a featheredge. The acrylic bond coat retains its adhesive strength even under damp exterior conditions.

SUITABLE FOR

Excellent for bonding new concrete to existing floors, walls or other sound surfaces such as metal or brick.

ADVANTAGES

- Improves adhesion strength and cures rapidly
- Increases bonding and reduces cracking
- Increases the bonding strength for patching or resurfacing concrete floors, driveways etc.
- Easier, more efficient mortar application

DIRECTIONS FOR USE

Surface preparation

A good, clean surface is very important. Remove all loose material and disintegrated concrete. All traces of oil, dust etc must be removed. The surface should be damp but do not leave standing water.

Product Code : BUCM

Mixing

Use 250ml **PYEACRYL CM** per 50kg cement and sand. Add **PYEACRYL CM** to the gauging water and mix well. The liquid admixture must be stirred before adding to the concrete mix in a clean container. To bond fresh concrete, apply a thin coat of full strength **PYEACRYL CM** by using brush or roller.

Note: Stir well before use.

TECHNICAL & PHYSICAL DATA

Colour	White
Form	Milky liquid
Odour	Pleasant sweet smell
Adhesion	Increases compressive, bond and flexural strength of concrete to steel.
Drying time	30mins - 1 hour
Coverage	250ml PYEACRYL CM in 50kg cement/ sand mix will cover approx. 15.5sq.m. at 6mm thickness.
Cleaning	Clean tools and equipment with water when wet.

PACKING

4 litres, 20 litres & 200 litres

Further information and advice are freely available from:

PYE PRODUCTS (M) SDN. BHD. (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



BUATAN MALAYSIA

All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.