



PYE Products..... *easy to use*



## PYEFIL GF 621

*Spray Plaster Grey Finish*

### DESCRIPTION

**PYEFIL GF 621** spray plasters are cement based water-resistant skim plasters formulated with special chemical additives that provide good workability, improved adhesion and durability. **PYEFIL** assists in correcting surface imperfections and gives a high quality plaster surface suitable for either painting, wallpapering or simply as a finish surface. Ceramic tiles or natural stones can be fixed on **PYEFIL** finished surface. **PYEFIL** is not recommended to be used on painted or non-cementitious surfaces.

### SUITABLE FOR

Concrete, cement rendered, panel, aerated light weight block or skim plastered surfaces.

### DIRECTIONS FOR USE

#### **Surface preparation**

Substrate must be clean, free of dust, oil, paint, grease and all traces of mould. Surface defects deeper than 4mm shall be patched/ repaired with cement renders or **PYEFIL** base plasters prior to the application. Prewetting is recommended for dry surfaces, but over wetting resulting in accumulation of water on the surface should be avoided.

#### **Mixing**

Add about 11 - 12 litres of water to 25kg of **PYEFIL** and mix with a power drill whisk or a suitable mechanical stirrer for 10 minutes to obtain a homogeneous creamy paste. Re-mix for 1 minute if the material is left undisturbed for more than 30 minutes.

**Product Code: PLGF**

### Application

Apply by using a spray plaster machine or directly with a steel trowel or spatula. Level out to a thickness of 1 - 2mm to obtain correct level or alignment. Allow the material to gain partial surface drying before returning to work on surface with a steel trowel to achieve a smooth finish. When applying several layers, the base layer must be dry before spreading the subsequent layer.

### TECHNICAL & PHYSICAL DATA

Colour	GF 621-Grey
Recommended thickness	1 - 2mm
Form	Powder
Pull out test	As per test report enclosed.
Coverage	1kg/mm/m <sup>2</sup>
Pot life	2 - 3 hours
Yield	Approx. 11 - 12 litres of water per 25kg bag.
Cleaning	Clean tools with clean water.
Fire hazard	Does not spread/ support fire.

### STORAGE

**PYEFIL** has a shelf life of 6 months, if kept in a dry and cool condition.

### PACKING

25kg/ bag

Further information and advice are freely available from:

**PYE PRODUCTS (M) SDN. BHD.** (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



95 ISO 9001 REG. NO. 831633-72



BUATAN MALAYSIA

*All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.*