

> PLASTER PRODUCTS



PYE Products..... easy to use

PYEPREMIX PLASTER N21

*Polymer Modified Premix Render Medium
Plaster for Interior and Exterior Use*

DESCRIPTION

PYEPREMIX PLASTER N21 cement based filling and leveling plasters formulated with special chemical additives to provide good workability, improved adhesion and durability.

PYEPREMIX PLASTER N21 assists in correcting surface imperfections. Ceramic tiles and natural stones can be fixed on a **PYEPREMIX PLASTER N21** finished surface. It is not recommended to be used on painted or other non-cementitious based substrates.

SUITABLE FOR

Concrete, hollow block and brickwalls.

DIRECTIONS FOR USE

Surface preparation

Substrate must be clean, free of dust, oil, paint, grease and all traces of mould. Prewetting is recommended for very dry surfaces, but over wetting resulting in accumulation of water on the surface should be avoided.

Mixing

Add about 6 - 7 liters of water to a 40kg bag of **PYEPREMIX PLASTER N21** and mix with a powered drill whisk or a suitable mechanical stirrer for 8 minutes to obtain a good trowel able consistency. Re-mix again for 1 minute if the material is left undisturbed for not more than 25 minutes.



Product Code : PLSN

Application

Apply by using a spray plaster machine or directly with a steel trowel or spatula. Level out to a thickness of 7 - 12mm to obtain the correct level or alignment. When applying several layers, the base layer must be dry before spreading the subsequent layer. **PYEPREMIX PLASTER N21** can be finished with a trowel or a sponge. For an extra smooth finished surface, apply one coat of **PYEFIL WF221** or **PYEFIL GF621** finish skim plaster to a thickness of 1 - 2mm.

TECHNICAL & PHYSICAL DATA

Colour	Light Grey
Recommended thickness	7 - 12mm
Form	Powder
Coverage	1.65kg/m ² /mm
Pot life	2 - 3 hours
Yield	Approx. 6 - 7 liters of clean water to a 40kg bag.
Cleaning	Clean tools with clean water.

STORAGE

PYEPREMIX PLASTER N21 has a shelf life of 6 months, if kept in a dry and cool condition.

PACKING

25kg or 40kg bag

Further information and advice are freely available from:

PYE PRODUCTS (M) SDN. BHD. (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



MS ISO 9001 REG. NO. 831638-12



BUATAN MALAYSIA

All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.