



PYE Products..... *easy to use*



PYETILEGROUT

Ready-Mixed Grout

DESCRIPTION

PYETILE GROUT is a ready mixed quick drying compound for grouting & sealing ceramic and mosaic wall/ floor tiles only.

- Ready to use
- Solvent free
- Can be tinted

SUITABLE FOR

PYETILE GROUT is suitable for use in tiled areas of kitchens, shower recesses, toilet walls and floors.

DIRECTIONS FOR USE

Surface preparation/ new work

Clean & dampen joints by rubbing up, down and across tiles. Use wet sponge, brush or cloth. Dry tile surfaces with clean cloth.

Surface preparation/ old work

Chisel out about 1/6" of old grout. Scrub surface thoroughly with kitchen cleanser. Clean & dampen joints by rubbing up, down and across tiles with wet sponge, brush or cloth. Dry tile surface with clean cloth.

Tinting

Grout can be tinted before use to match colored tile using any latex base or universal colorant.

Product Code : WATI

Application

Work grout thoroughly into each joint with a sponge, float or finger. Wait 10 minutes for grout to set, then remove excess by lightly wiping diagonally across each joint with a sponge or cloth. Close cap tightly after use.

Finishing

When grout is firm (about 1 hour) polish with clean dry cloth. Allow to dry 16 - 24 hours before exposure to water.

Clean up

Clean tools and hands with water before grout dries.

TECHNICAL & PHYSICAL DATA

Colour	White, Grey
Adhesion	Excellent adhesion to concrete, masonry and asbestos cement.
Drying time	1 - 2 hours under normal conditions.
Coverage	Approx. 2sq.m. of tiles per kg.
Cleaning	Clean all equipment with water before setting occurs.

PACKING

500gm

Further information and advice are freely available from:

PYE PRODUCTS (M) SDN. BHD. (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.