

> TILING PRODUCTS



PYE Products..... easy to use



PYE FIX

Cement-Based Tile Adhesive C2

DESCRIPTION

PYE FIX is a thin-bed cement-based adhesive for the fixing of ceramic floor, wall tiles and mosaics. It has been specially formulated for use over sand/ cement render, is non-toxic, easy to apply and no wetting of tiles is required when fixing. It is considerably lighter in comparison with conventional sand/ cement mortar and the final weight of the finished installation is proportionately reduced.

SUITABLE FOR

PYE FIX is ideal for fixing ceramic tiles, mosaics and quarry tiles in bathrooms, kitchens, laundry, family rooms, entrance halls and outdoor living areas on concrete, cement render and brick work. **DO NOT** use **PYE FIX** on gypsum, wood or metal substrates.

DIRECTIONS FOR USE

Surface preparation

The surfaces to be tiled must be firm and clean from dust, paint and other contaminants. Steel float concrete floors must be acid etched prior to tiling.

Mixing

Mix the 25kg powder with 25% of clean water to a creamy consistency. Mix sufficient to last 30 - 60 minutes. Allow mixture to stand for 8 - 10 minutes. Mixture should be used within 2 hours.

Application

Sand/ cement render should be left with a woodfloat finish. It must be clean and free from dust and oil. Allow 7 days after rendering before fixing tiles with **PYE FIX**. Use a notched trowel to spread the adhesive on the surface to a thickness of about 3mm for flat-backed ceramic tiles. Tiles with grooves, ridges or knobs on the

Product Code : WAFX

back should be laid using 6mm x 6mm notched trowel. Press tiles in place with a twisting motion. Firmly tap the tile with the handle of a hammer or rubber mallet whilst positioning the tiles. When laying large areas, ensure that expansion joints are incorporated in the design stage.

Do not spread more than 1sq. metre at a time. Should the adhesive dry up due to a long delay, remove the adhesive and comb out a fresh layer. Do not soak tiles in water.

TECHNICAL & PHYSICAL DATA

Colour	Dark grey when wet, light grey when dry.
Odour	Odourless when dry.
Drying time	6 hours
Form	Powder
Coverage	About 3kg per sq metre (3mm thickness).
Grouting	Grouting should commence at least 24 hours after completion of tiling. PYE GROUT used as the grouting provided the joint between the tiles is not less than 3mm in width.
Cleaning	Clean tools with water after use.

PACKING

1kg & 25kg

Further information and advice are freely available from:

PYE PRODUCTS (M) SDN. BHD. (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.