

> TILING PRODUCTS



PYE Products..... easy to use



## PYEMULTI-FIX

Cement-Based Tile Adhesive

### DESCRIPTION

**PYEMULTI-FIX TILE ADHESIVE** is a cement-based adhesive suitable for cement surfaces for the fixing of ceramic floor, quarry tiles and mosaics. It is easy to apply and no wetting of tiles is required when fixing. For tiling of the wall surfaces, **PYEFIX** is recommended as it has a stronger adhesive property.

### SUITABLE FOR

**PYEMULTI-FIX** is ideal for fixing ceramic tiles, mosaics and quarry tiles in bathrooms, kitchens, laundry, family rooms, entrance halls and outdoor living areas on concrete, cement render and brick work.

DO NOT use **PYEMULTI-FIX** on gypsum, wood or metal substrates.

### DIRECTIONS FOR USE

#### Surface preparation

The surfaces to be tiled must be firm and clean from dust, paint and other contaminates. Steel float concrete floors must be acid etched prior to tiling.

#### Mixing

Mix the 25kg powder with 25% of clean water to a creamy consistency. Mix sufficient to last 30 - 60 minutes. Allow mixture to stand for 8 - 10 minutes. Mixture should be used within 2 hours.

#### Application

Sand/ cement render should be left with a woodfloat finish. It must be clean and free from dust and oil. Allow 7 days after rendering before fixing tiles with **PYEMULTI-FIX**. Use a notched trowel to spread the adhesive on the surface to a thickness of about 3mm for flat-backed ceramic tiles. Tiles with grooves, ridges or knobs on the back should be laid using 6mm x 6mm notched

Product Code : WAMU

trowel. Press tiles in place with a twisting motion. Firmly tap the tile with the handle of a hammer or rubber mallet whilst positioning the tiles. When laying large areas, ensure that expansion joints are incorporated in the design stage. Do not spread more than 1 sq. metre at a time. Should the adhesive dry up due to a long delay, remove the adhesive and comb out a fresh layer. Do not soak tiles in water.

### TECHNICAL & PHYSICAL DATA

|             |   |
|-------------|---|
| Colour      | Dark grey when wet, light grey when dry.  |
| Form        | Powder  |
| Odour       | Odourless when dry.   |
| Drying time | 6 hours   |
| Shelf life  | Minimum of 12 months under cool, dry conditions.  |
| Coverage    | About 3kg per sq. metre (3mm thickness).  |
| Grouting    | Grouting should commence at least 24 hours after completion of tiling.<br><b>PYEFLOORFIX</b> can also be used as the grouting provide the joint between the tiles is not less than 1.75mm in width. For best results, use <b>PYEGROUT</b> for grouting. |
| Cleaning    | Clean tools with water after use.   |

### PACKING

20kg & 25kg

Further information and advice are freely available from:

**PYE PRODUCTS (M) SDN. BHD.** (Co. No. 206933-D)

Lot 4993, 5½ Mile Jalan Meru, 41050 Klang, Selangor Darul Ehsan, Malaysia.

Tel : 603-3392 8104, 3392 8112 Fax : 603-3392 8097

E-mail : enquiry@pyeproducts.com Website : www.pyeproducts.com



All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.